

LED Clear C37 Bulb



Features:



- Patented optical design with clear cover
- Insulated and eco-friendly heat sinking design
- Dimmable version optional
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | Clear C37 WP25T4 | Clear DC37 WP25T4 |
|-------------------------------------|------------------|-------------------|
| Watt (W) | 3.5 | 4 |
| Comparable Incandescent Wattage (W) | 25 | 25 |
| CCT (K) | 2700K * | 2700K * |
| Luminous Flux (lm) | 250 | 250 |
| Energy Efficiency Classes | A+ | A+ |
| Luminous Efficiency (lm/W) | 70 | 65 |
| Voltage (V) | AC220-240V | AC220-240V |
| CRI (Ra) | 80 | 80 |
| Dimmable | No | Yes |
| Socket | E14(E27/B22) | E14(E27/B22) |
| Lifetime (hrs) | 25,000 | 25,000 |
| Weight (g) | 65 | 65 |

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor

Bedroom

Hotel

Restaurant

LED Clear F37 Bulb



Features:

- Patented optical design with clear cover
- Insulated and eco-friendly heat sinking design
- Dimmable version optional
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | Clear F37 WP25T4 | Clear DF37 WP25T4 |
|-------------------------------------|------------------|-------------------|
| Watt (W) | 3.5 | 4 |
| Comparable Incandescent Wattage (W) | 25 | 25 |
| CCT (K) | 2700K * | 2700K * |
| Luminous Flux (lm) | 250 | 250 |
| Energy Efficiency Classes | A+ | A+ |
| Luminous Efficiency (lm/W) | 70 | 65 |
| Voltage (V) | AC220-240V | AC220-240V |
| CRI (Ra) | 80 | 80 |
| Dimmable | No | Yes |
| Socket | E14(E27/B22) | E14(E27/B22) |
| Lifetime (hrs) | 25,000 | 25,000 |
| Weight (g) | 65 | 65 |
| Mechanical Drawing | | |
| Photometric Diagrams | | |

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED Clear P45 Bulb



Features:

- Patented optical design with clear cover
- Insulated and eco-friendly heat sinking design
- Dimmable version optional
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | Clear P45 WP25T4 | Clear DP45 WP25T4 |
|-------------------------------------|------------------|-------------------|
| Watt (W) | 3.5 | 4 |
| Comparable Incandescent Wattage (W) | 25 | 25 |
| CCT (K) | 2700K * | 2700K * |
| Luminous Flux (lm) | 250 | 250 |
| Energy Efficiency Classes | A+ | A+ |
| Luminous Efficiency (lm/W) | 70 | 65 |
| Voltage (V) | AC220-240V | AC220-240V |
| CRI (Ra) | 80 | 80 |
| Dimmable | No | Yes |
| Socket | E14 | E14 |
| Lifetime (hrs) | 25,000 | 25,000 |
| Weight (g) | 60 | 60 |
| Mechanical Drawing | | |
| Photometric Diagrams | | |

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor



Bedroom



Hotel



Restaurant

LED C37 Bulb



Features:



- Insulated and eco-friendly heat sinking design
- Ra 97 nearly close to incandescent lighting effect
- 2500K/2700K available
- Dimmable version optional
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | C37 K2F25T4 | C37 K2F25T4 | DC37 K2P25T4 |
|-------------------------------------|--------------|--------------|--------------|
| Watt (W) | 4 | 4 | 4 |
| Comparable Incandescent Wattage (W) | 25 | 25 | 25 |
| CCT (K) | 2500K * | 2700K * | 2700K * |
| Luminous Flux (lm) | 250 | 250 | 250 |
| Energy Efficiency Classes | A+ | A+ | A+ |
| Luminous Efficiency (lm/W) | 65 | 65 | 65 |
| Voltage (V) | AC220-240V | AC220-240V | AC220-240V |
| CRI (Ra) | 97 | 97 | 90 |
| Dimmable | No | No | Yes |
| Socket | E14(E27/B22) | E14(E27/B22) | E14(E27/B22) |
| Beam Angle (deg) | 250 | 250 | 220 |
| Lifetime (hrs) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 55 | 55 | 55 |

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor

Bedroom

Hotel

Restaurant

LED F37 Bulb



Features:



- Insulated and eco-friendly heat sinking design
- Ra 97 nearly close to incandescent lighting effect
- 2500K/2700K available
- Dimmable version optional
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | F37 K2P25T4 | F37 K2F25T4 | DF37 K2P25T4 |
|-------------------------------------|--------------|--------------|--------------|
| Watt (W) | 4 | 4 | 4 |
| Comparable Incandescent Wattage (W) | 25 | 25 | 25 |
| CCT (K) | 2500K * | 2700K * | 2700K * |
| Luminous Flux (lm) | 250 | 250 | 250 |
| Energy Efficiency Classes | A+ | A+ | A+ |
| Luminous Efficiency (lm/W) | 65 | 65 | 65 |
| Voltage (V) | AC220-240V | AC220-240V | AC220-240V |
| CRI (Ra) | 97 | 97 | 90 |
| Dimmable | No | No | Yes |
| Socket | E14(E27/B22) | E14(E27/B22) | E14(E27/B22) |
| Beam Angle (deg) | 250 | 250 | 220 |
| Lifetime (hrs) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 55 | 55 | 55 |

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED P45 Bulb



Features:



- Insulated and eco-friendly heat sinking design
- Ra 97 nearly close to incandescent lighting effect
- 2500K/2700K available
- Dimmable version optional
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | P45 K2F25T4 | P45 K2F25T4 | DP45 K2F25T4 |
|-------------------------------------|-------------|-------------|--------------|
| Watt (W) | 4 | 4 | 4 |
| Comparable Incandescent Wattage (W) | 25 | 25 | 25 |
| CCT (K) | 2500K * | 2700K * | 2700K * |
| Luminous Flux (lm) | 250 | 250 | 250 |
| Energy Efficiency Classes | A+ | A+ | A+ |
| Luminous Efficiency (lm/W) | 65 | 65 | 65 |
| Voltage (V) | AC220-240V | AC220-240V | AC220-240V |
| CRI (Ra) | 97 | 97 | 90 |
| Dimmable | No | No | Yes |
| Socket | E14 | E14 | E14 |
| Beam Angle (deg) | 170 | 170 | 170 |
| Lifetime (hrs) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 52 | 52 | 52 |

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor

Bedroom

Hotel

Restaurant

LED Clear C37 Bulb



Features:



- Insulated and eco-friendly heat sinking design
- 3.0W equivalent to 25W incandescent bulb
- Patented optical design with 270°sparkling lighting effect
- Golden and silver metal available
- CE and RoHS compliant

Cautions:

- Non-dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | C37 KF25T3 | C37 NF25T3 | C37 DF25T3 |
|-------------------------------------|------------|------------|------------|
| Watt (W) | 3 | 3 | 3 |
| Comparable Incandescent Wattage (W) | 25 | 25 | 25 |
| CCT (K) | 2700K * | 4000K * | 5300K * |
| Luminous Flux (lm) | 250 | 250 | 250 |
| Energy Efficiency Classes | A+ | A+ | A+ |
| Luminous Efficiency (lm/W) | 83 | 83 | 83 |
| Voltage (V) | AC220-240V | AC220-240V | AC220-240V |
| CRI (Ra) | 80 | 80 | 80 |
| Dimmable | No | No | No |
| Socket | E14 | E14 | E14 |
| Beam Angle (deg) | 240 | 240 | 240 |
| Lifetime (hrs) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 54 | 54 | 54 |

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor

Bedroom

Hotel

Restaurant

LED Diamond C37 Bulb



Features:

- 5.5W equivalent to 35W incandescent bulb
- Patented optical design with 270°
- sparkling lighting effect
- Good heat sinking without lamp shade
- Insulated switching power supply
- Silver and Golden finishing available
- Dimmable version optional
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Not for use in totally enclosed recessed fixtures
- Not intended for use with emergency exit fixtures or emergency lights
- Consult competent electricians for technical support

| Part No. | Diamond C37 KP35T6 | Diamond DC37 KP40T7 |
|-------------------------------------|--------------------|---------------------|
| Watt (W) | 5.5 | 7 |
| Comparable Incandescent Wattage (W) | 35 | 40 |
| CCT (K) | 2700K * | 2700K * |
| Luminous Flux (lm) | 325 | 420 |
| Energy Efficiency Classes | A+ | A+ |
| Luminous Efficiency (lm/W) | 60 | 60 |
| Voltage (V) | AC220-240V | AC220-240V |
| CRI (Ra) | 80 | 80 |
| Dimmable | No | Yes |
| Socket | E14 | E14 |
| Lifetime (hrs) | 25,000 | 25,000 |
| Weight (g) | 54 | 54 |
| Mechanical Drawing | | |
| Photometric Diagrams | | |

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED C37 FLORA Bulb



Features:



- Insulated and eco-friendly ceramic heat sinking design
- Ra 97 SUNWHITE Technology, R9 90, nearly close to incandescent lighting effect, 2500K/2700K available
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Don't use it in sealed fixture

| Part No. | C37 K2F40T6 | C37 K2F40T6 | DC37 K2F40T6 |
|-------------------------------------|-------------|-------------|--------------|
| Watt (W) | 6 | 6 | 6 |
| Comparable Incandescent Wattage (W) | 40 | 40 | 40 |
| CCT (K) | 2500K * | 2700K * | 2700K * |
| Luminous Flux (lm) | 470 | 470 | 470 |
| Energy Efficiency Classes | A+ | A+ | A+ |
| Luminous Efficiency (lm/W) | 80 | 80 | 80 |
| Voltage (V) | AC220-240V | AC220-240V | AC220-240V |
| CRI (Ra) | 97 | 97 | 90 |
| Dimmable | No | No | Yes |
| Socket | E14/E27/B22 | E14/E27/B22 | E14/E27/B22 |
| Beam Angle (deg) | 200 | 200 | 200 |
| Lifetime (hrs) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 60 | 60 | 60 |

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor

Bedroom

Hotel

Restaurant

LED P45 Bulb



Features:



- Smart heat sink design
- Ra 97 nearly close to incandescent lighting effect
- 6W equivalent to 40W incandescent bulb
- Dimmable version optional
- 85% energy saving
- 2500K/2700K available
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | P45 K2F40T6 | P45 K2F40T6 | DP45 K2F40T6 |
|-------------------------------------|-------------|-------------|--------------|
| Watt (W) | 6 | 6 | 6 |
| Comparable Incandescent Wattage (W) | 40 | 40 | 40 |
| CCT (K) | 2500K * | 2700K * | 2700K * |
| Luminous Flux (lm) | 470 | 470 | 470 |
| Energy Efficiency Classes | A+ | A+ | A+ |
| Luminous Efficiency (lm/W) | 80 | 80 | 80 |
| Voltage (V) | AC220-240V | AC220-240V | AC220-240V |
| CRI (Ra) | 97 | 97 | 90 |
| Dimmable | No | No | Yes |
| Socket | E14 | E14 | E14 |
| Beam Angle (deg) | 130 | 130 | 130 |
| Lifetime (hrs) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 62 | 62 | 62 |

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED T26 Bulb

LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light



Features:

- Ceramic heat sink
- 5W equivalent to 15W incandescent bulb
- 85% energy saving
- Ra90 (2700K)
- CE and RoHS compliant

Cautions:

- Non-dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | T26 K2F05T1 |
|-------------------------------------|-------------|
| Watt (W) | 1 |
| Comparable Incandescent Wattage (W) | 5 |
| CCT (K) | 2500K * |
| Luminous Flux (lm) | 50 |
| Energy Efficiency Classes | A+ |
| Luminous Efficiency (lm/W) | 50 |
| Voltage (V) | AC220-240V |
| CRI (Ra) | 90 |
| Dimmable | No |
| Socket | E14 |
| Beam Angle (deg) | 120 |
| Lifetime (hrs) | 25,000 |
| Weight (g) | 11 |
| Mechanical Drawing | |
| Photometric Diagrams | |

* 3000K / 4000K / 5300K also available

Application:

- Home, villa and other residential buildings
- Hotels, restaurants, hospital, office
- Government buildings



Indoor

Bedroom

Hotel

Restaurant

LED T26 Bulb



Features:



- Ceramic heat sink
- 2W equivalent to 15W incandescent bulb
- 85% energy saving
- Ra90 (2700K)
- CE and RoHS compliant

Cautions:

- Non-dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | T26 K3F10F1 | T26 WF15T2 |
|-------------------------------------|-------------|------------|
| Watt (W) | 1 | 2 |
| Comparable Incandescent Wattage (W) | 10 | 15 |
| CCT (K) | 2700K * | 3000K * |
| Luminous Flux (lm) | 90 | 136 |
| Energy Efficiency Classes | A+ | A |
| Luminous Efficiency (lm/W) | 90 | 68 |
| Voltage (V) | DC12V | AC220-240V |
| CRI (Ra) | 90 | 80 |
| Dimmable | No | No |
| Socket | E14 | E14 |
| Beam Angle (deg) | 120 | 130 |
| Lifetime (hrs) | 25,000 | 25,000 |
| Weight (g) | 21 | 22 |

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Home, villa and other residential buildings
- Hotels, restaurants, hospital, office
- Government buildings



LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light