

LED Clear G45 Bulb



Features:

- Patented optical design with clear cover
- Insulated and eco-friendly heat sinking design
- Dimmable version optional
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	Clear G45 WP25T4	Clear DG45 WP25T4
Watt (W)	3.5	4
Comparable Incandescent Wattage (W)	25	25
CCT (K)	2700K *	2700K *
Luminous Flux (lm)	250	250
Energy Efficiency Classes	A+	A+
Luminous Efficiency (lm/W)	70	65
Voltage (V)	AC220-240V	AC220-240V
CRI (Ra)	80	80
Dimmable	No	Yes
Socket	E27/B22	E27/B22
Lifetime (hrs)	25,000	25,000
Weight (g)	70	70
Mechanical Drawing		
Photometric Diagrams		

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED G45 Bulb



Features:



- Insulated and eco-friendly heat sinking design
- Ra 97 nearly close to incandescent lighting effect
- 2500K/2700K available
- Dimmable version optional
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	G45 K2F25T4	G45 K2F25T4	DG45 K2F25T4
Watt (W)	4	4	4
Comparable Incandescent Wattage (W)	25	25	25
CCT (K)	2500K *	2700K *	2700K *
Luminous Flux (lm)	250	250	250
Energy Efficiency Classes	A+	A+	A+
Luminous Efficiency (lm/W)	65	65	65
Voltage (V)	AC220-240V	AC220-240V	AC220-240V
CRI (Ra)	97	97	90
Dimmable	No	No	Yes
Socket	E27/B22	E27/B22	E27/B22
Beam Angle (deg)	170	170	170
Lifetime (hrs)	25,000	25,000	25,000
Weight (g)	58	58	58

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED FLORA G45 Bulb



Features:



- FLORA heat sink design
- Ra 97 nearly close to incandescent lighting effect
- 6W equivalent to 40W incandescent bulb
- Dimmable version optional
- 85% energy saving
- 2500K/2700K available
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	G45 K2F40T6	G45 K2F40T6	DG45 K2F40T6
Watt (W)	6	6	6
Comparable Incandescent Wattage (W)	40	40	40
CCT (K)	2500K *	2700K *	2700K *
Luminous Flux (lm)	470	470	470
Energy Efficiency Classes	A+	A+	A+
Luminous Efficiency (lm/W)	80	80	80
Voltage (V)	AC220-240V	AC220-240V	AC220-240V
CRI (Ra)	97	97	90
Dimmable	No	No	Yes
Socket	E27/B22	E27/B22	E27/B22
Beam Angle (deg)	150	150	150
Lifetime (hrs)	25,000	25,000	25,000
Weight (g)	66	66	66

Mechanical Drawing



Photometric Diagrams

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor



Bedroom



Hotel



Restaurant

LED A55 Bulb





Features:

- 7W equivalent to 40W incandescent bulb
- Insulated and eco-friendly heat sinking design
- Beam angle: 270°
- 3000K/4000K/5300K also available
- Switching power supply
- CE and RoHS compliant

Cautions:

- Non-dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	A55 KF40T7
Watt (W)	7
Comparable Incandescent Wattage (W)	40
CCT (K)	2700K *
Luminous Flux (lm)	470
Energy Efficiency Classes	A+
Luminous Efficiency (lm/W)	70
Voltage (V)	AC220-240V
CRI (Ra)	80
Dimmable	No
Socket	E27/B22
Beam Angle (deg)	270
Lifetime (hrs)	25,000
Weight (g)	50
Mechanical Drawing	
Photometric Diagrams	

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED A60 Bulb





Features:

- Insulated and EC heat sinking design
- 2700K
- Ra 97
- Switching power supply
- CE and RoHS compliant

Cautions:

- Non-dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	A60 K2F40T7
Watt (W)	6.5
Comparable Incandescent Wattage (W)	40
CCT (K)	2700K
Luminous Flux (lm)	470
Energy Efficiency Classes	A+
Luminous Efficiency (lm/W)	70
Voltage (V)	AC220-240V
CRI (Ra)	97
Dimmable	No
Socket	E27/B22
Beam Angle (deg)	240
Lifetime (hrs)	25,000
Weight (g)	110
Mechanical Drawing	
Photometric Diagrams	

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor



Bedroom



Hotel



Restaurant

LED A60 Bulb



Features:

- Insulated and EC heat sinking design
- 2700K
- Ra 97
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	DA60 K2F40T7
Watt (W)	6.5
Comparable Incandescent Wattage (W)	40
CCT (K)	2700K
Luminous Flux (lm)	470
Energy Efficiency Classes	A+
Luminous Efficiency (lm/W)	70
Voltage (V)	AC220-240V
CRI (Ra)	97
Dimmable	Yes
Socket	E27/B22
Beam Angle (deg)	240
Lifetime (hrs)	25,000
Weight (g)	110
Mechanical Drawing	
Photometric Diagrams	

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor



Bedroom



Hotel



Restaurant

LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED A60 Bulb



Features:

- Good heat sinking design
- Beam angle: 240deg
- 85% energy saving
- Switching power supply

Cautions:

- Non-dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	A60 K2F60T11
Watt (W)	11
Comparable Incandescent Wattage (W)	60
CCT (K)	2700K *
Luminous Flux (lm)	810
Energy Efficiency Classes	A+
Luminous Efficiency (lm/W)	75
Voltage (V)	AC220-240V
CRI (Ra)	97
Dimmable	No
Socket	E27/B22
Beam Angle (deg)	240
Lifetime (hrs)	25,000
Weight (g)	165
Mechanical Drawing	
Photometric Diagrams	

* 3000K / 4000K / 5300K also available

Application:

- Villa, home, residential buildings
- Hotels, restaurants, bars



LED A60 Bulb



Features:

- Good heat sinking design
- Beam angle: 240deg
- 85% energy saving
- Switching power supply

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	DA60 K2F60T11
Watt (W)	11
Comparable Incandescent Wattage (W)	60
CCT (K)	2700K *
Luminous Flux (lm)	810
Energy Efficiency Classes	A+
Luminous Efficiency (lm/W)	75
Voltage (V)	AC220-240V
CRI (Ra)	97
Dimmable	Yes
Socket	E27/B22
Beam Angle (deg)	240
Lifetime (hrs)	25,000
Weight (g)	165
Mechanical Drawing	
Photometric Diagrams	

* 3000K / 4000K / 5300K also available

Application:

- Villa, home, residential buildings
- Hotels, restaurants, bars



Indoor



Bedroom



Hotel



Restaurant

LED Tube

LED luminaire

LED Bulb

LED Spotlight

LED PAR Light

LED A65 FLORA Bulb



Features:

- FLORA design with excellent heat sinking performance
- 13W equivalent to 75W incandescent bulb respectively
- 85% energy saving
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	DA65 K2F75T13
Watt (W)	13
Comparable Incandescent Wattage (W)	75
CCT (K)	2700K *
Luminous Flux (lm)	1050
Energy Efficiency Classes	A+
Luminous Efficiency (lm/W)	81
Voltage (V)	AC220-240V
CRI (Ra)	90
Dimmable	Yes
Socket	E27/B22
Beam Angle (deg)	140
Lifetime (hrs)	25,000
Weight (g)	163
Mechanical Drawing	
Photometric Diagrams	

* 3000K / 4000K / 5300K also available

Application:

- Home, villa and other residential buildings
- Hotels, restaurants, hospital, office
- Government buildings



Indoor



Bedroom



Hotel



Restaurant

LED A65 FLORA Bulb



Features:

- FLORA design with excellent heat sinking performance
- 15W equivalent to 100W incandescent bulb respectively
- 85% energy saving
- Switching power supply
- CE and RoHS compliant

Cautions:

- Non-dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	A65 K2F100T15
Watt (W)	15
Comparable Incandescent Wattage (W)	100
CCT (K)	2700K *
Luminous Flux (lm)	1521
Energy Efficiency Classes	A+
Luminous Efficiency (lm/W)	100
Voltage (V)	AC220-240V
CRI (Ra)	90
Dimmable	No
Socket	E27/B22
Beam Angle (deg)	140
Lifetime (hrs)	25,000
Weight (g)	163
Mechanical Drawing	
Photometric Diagrams	

* 3000K / 4000K / 5300K also available

Application:

- Home, villa and other residential buildings
- Hotels, restaurants, hospital, office
- Government buildings



LED Tube

LED Luminaire

LED Bulb

LED Spotlight

LED PAR Light